

Partner of the European
PCB Industry



MULTILAYERS PRESSING

Release Film

Pacothane, Pacolon, Paco-Via



Press pads

Press Pads: Pacopads, Pacotherm & PressProbe



Conformal

Conformal : Pacoplus, pacocore, Pacoflex



Auxiliaries

Kraft Press Pad

Description: Blue Kraft ensuring uniform heat rise.

Properties: Weight: 350 gr/m²

Sheet sizes: 940x1245 mm; 610x610 mm; 710x710 mm

Panels cut to size and punched available

Silicon Rubber Press Pad

Description: Provide uniform cushioning and precise control over heat rise and long life (up to 150 uses) and faster lay-up. Put talcum powder before use.

Properties: Cured re-enforced silicone red rubber on both sides

Average pad life: 150 cycles (temperature and time dependant)

Product Operating Temperature: 204°C (400°F)

Overall thickness: 1,15 mm (.045")

Width: 1270 mm

Teflon Release film

Description: High temperature application release film. Offers outstanding heat and chemical resistance, high dielectric strength and anti-stick properties

Dimensions: Roll: Width: 508 mm, Length: 150 m

Thickness: 3 and 4 mils

Pressure Revealing Films

Description: Provides a quick, simple and accurate in-house procedure for checking for "high" and "low" pressure zones due to (1) press platen misalignments or (2) the design configuration (pads, high density circuitry, ground planes, etc.) of the circuit board itself. Pressures, distributed unevenly, can lead to circuit board manufacturing problems and rejects. It will help the laminator view potential pressure-related laminating problems even before they occur.

Tooling

Lamination tooling and transport plates; Alignmentpins and bushing;
Resin Release Agent...

